

AD-384r6

Overview

Frequency Band

UHF 860 - 960 MHz

Chip

Impinj Monza R6

Antenna Dimensions

50 x 30 mm / 1.97 x 1.18 in

International Standard

ISO/IEC 18000-63 Type C

Industry Segments

Apparel
Logistics

Applications

Supply Chain Management
Home Essentials
Brand Protection

RoHs

EU Directive 2011/65/EU and
2015/863 Compliant



High performance on a multitude of items

AD-384r6 and AD-384r6-P inlays from Avery Dennison are high performing Gen2 UHF RFID products that are available in two chip formats: Monza r6 and Monza r6-P.

Both are wide-edge leading inlays that are suitable for a wide variety of RFID tagging applications, including supply chain, inventory & logistics, apparel and home essentials.


AD-384r6 with the Impinj Monza R6 IC comes with 96 bit EPC memory, while AD-384r6-P with the Impinj Monza R6-P is available with 128/96-bit EPC memory and 32/64-bit user memory. Both versions have a 48-bit unique serialized TID Number and are available in Dry Inlay, Wet Inlay and Label / sticker delivery formats.

Like all RFID products from Avery Dennison, AD-384r6 and AD-384r6-P inlays are manufactured according to the industry's highest quality standards, as confirmed by the RFID Lab at Auburn University: The inspection body awarded Avery Dennison its first comprehensive and significant ARC accreditation for quality.


Technical features

Chip	Impinj Monza R6		
EPC and User Memory	96-bit and n/a	96-bit and n/a	96-bit and n/a
TID Memory	48-bit		
Product Code	RF600872	RF600873	RF100411
Delivery Format	Dry inlay	Wet inlay	Label / sticker
Die-cut Dimension	-	54 x 34 mm / 2.13 x 1.34 in	57 x 38 mm / 2.25 x 1.50 in
Inlay Substrate	Opaque PET	Opaque PET	40# DC
Face Sheet	-	-	TT2C (FASSON®) Bright White
Total Thickness	9 - 11 mils / 229 - 279 microns	10 - 12 mils / 254 - 305 microns	11 - 14 mils / 280 - 355 microns
Standard Pitch	38.1 mm / 1.5 in	38.1 mm / 1.5 in	50.8 mm / 2 in
Web Width	54 mm / 2 in	58 mm / 2 in	61.2 mm / 2 in
Core Size	76 mm / 3 in		
Quantity / Reel	15000 pcs/reel	10000 pcs/reel	2461 pcs/reel
Operating Temperature	-40 °C to 85 °C -40 °F to 185 °F		
On-Metal	Non metal		
Certificate	ARC		

Orientation sensitivity



Read range



All graphs are indicative: performance in real life applications may vary.

Contact information

rfid.averydennison.com/contact

North America: +1-866-903-7343 (toll free US)

International: +1-678-617-2359

RoHS

© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

