# AD Frog M4QT ETSI

#### Overview

Frequency Band UHF 860 - 960 MHz

**Chip** Impinj Monza 4QT

**Antenna Dimensions** 40 x 40 mm / 1.58 x 1.58 in

International Standard ISO 18000-63, G2V2

Industry Segments Logistics

**Applications** Asset Tracking Package tracking

RoHS

EU Directive 2011/65/EC and Directive (EU) 2015/863

REACH Regulation (EC) No. 1907/2006



## High performance product for supply chain applications

Avery Dennison's Frog M4QT inlays and tags are designed for pallet and case level applications offering high performance in supply chain management applications.

AD Frog M4QT products have a small, cost-efficient True3D form factor with complete orientation insensitivity providing consistent performance even on challenging materials. High performance Frog M4QT inlays deliver excellent read range and are compatible with the Impinj Monza 4 IC family.

AD Frog M4QT tags and inlays are produced using leading-edge inlay assembly technologies. Monitoring every step in the production process, from the antenna to the final assembly of the inlay, guarantees optimal quality products.

Avery Dennison's inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-theart product that meets a variety of application needs, enhancing RFID usage for difficult-to-tag materials.




#### **Technical features**

Chip	Impinj Monza 4QT
EPC and User Memory	128-bit / 512-bit
TID Memory	96-bit / 48-bit unique serial number
Product Code	3006928 / IL-603314
Delivery Format	Wet inlay+
Die-Cut Dimension	43 x 43 mm / 1.69 x 1.69 in
Inlay Substrate	PET
Face Sheet	Clear PET12
Standard Pitch	50 mm / 2 in
Web Width	50 mm / 2 in
Core Size	76 mm / 3 in
Quantity / Reel	5,000 pcs/reel 10,000 pcs/box
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F

Orientation sensitivity

### Read range



All graphs are indicative: performance in real life applications may vary.

#### **Contact information**

rfid.averydennison.com/contact North America: +1-866-903-7343 (toll free US) International: +1-678-617-2359



Connect with us on:



© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions
Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact
and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

