

AD Accessory Tag M730

Overview

Frequency Band

UHF 860 - 960 MHz

Chip

Impinj M730

Antenna Dimensions

30 x 15 mm / 1.20 x 0.60 in

International Standard

ISO 18000-63, EPC Class 1 Gen 2

Industry Segments

Apparel
Healthcare

Applications

Children Accessories
Fashion Jewelry and Sunglasses
Pharmaceutical and Healthcare

RoHS

EU Directive 2011/65/EC and
Directive (EU) 2015/863

REACH

Regulation (EC) No. 1907/2006



Ideal for small item-level tagging

Our AD Accessory M730 inlays and tags are optimized for accessory and cosmetics applications and small item tagging, offering excellent performance and superior close-coupling features.


AD Accessory products have a 30 x 15 mm antenna design providing superior bulk reading performance when attached to small items and feature M730 chips from Impinj. The chip is equipped with 128-bit of EPC memory and a 96-bit Tag Identifier (TID) with a 48-bit unique serial number factory-encoded into the TID. With a compact 33 mm (1.3 inch) form factor, easily convertible into end-application usage, they are available in dry, wet and paper tag delivery formats.

Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment.


Technical features

Chip	Impinj M730		
EPC and User Memory	128-bit / 0-bit		
TID Memory	96-bit / 48-bit unique serial number		
Product Code	3008300	3008304	3008305
Delivery Format	Dry inlay	Wet inlay	Label
Die-Cut Dimension	-	33 x 18 mm / 1.30 x 0.70 in	33 x 18 mm / 1.30 x 0.70 in
Inlay Substrate	PET	PET	PET
Face Sheet	No face	Clear PET	Mid-gloss paper
Standard Pitch	20 mm / 0.787 in	20 mm / 0.787 in	20 mm / 0.787 in
Web Width	36 mm / 1.4 in	36 mm / 1.4 in	36 mm / 1.4 in
Core Size	76 mm / 3 in	76 mm / 3 in	76 mm / 3 in
Quantity / Reel	10,000 pcs/reel 20,000 pcs/box	10,000 pcs/reel 30,000 pcs/box	5,000 pcs/reel 15,000 pcs/box
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F		
Certification	ARC spec Q		

Orientation sensitivity



Read range



All graphs are indicative: performance in real life applications may vary.

Contact information

rfid.averydennison.com/contact
 +1-678-617-2359

Connect with us on:



© 2022 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

